



How fractal texture segmentation turns out to be a strongly convex optimization problem ?[†].

B. Pascal¹, N. Pustelnik¹, P. Abry¹

Laboratoire CRISyAL, Lille
March, 3rd 2020

¹ Univ Lyon, ENS de Lyon, Univ Claude Bernard Lyon 1, CNRS,
Laboratoire de Physique, F-69342 Lyon, France, firstname.lastname@ens-lyon.fr

[†] Supported by Defi Imag'in SIROCCO and ANR-16-CE33-0020 MultiFracs, France.

Describing and interpreting real-world images

Texture as a discriminating feature






Describing and interpreting real-world images

Texture as a discriminating feature





Describing and interpreting real-world images

Texture as a discriminating feature



Describing and interpreting real-world images



Texture as a discriminating feature



Texture is of utmost importance in complex computer vision tasks.


Describing and interpreting real-world images

Texture as a discriminating feature




Texture is of utmost importance in complex computer vision tasks.
fractal segmentation

Formulation of the texture segmentation problem



Formulation of the texture segmentation problem



Purpose: obtaining a partition of the image into κ homogeneous regions

$$\Omega = \Omega_1 \sqcup \dots \sqcup \Omega_\kappa$$



Ω_k : pixels corresponding to texture k .

Outline – Fractal texture segmentation

1. Fractal texture model
2. Attributes estimation and segmentation
3. Multiphasic flow segmentation
4. Regularization parameters tuning


Texture's attributes definition

Piecewise monofractal model




Texture's attributes definition

Piecewise monofractal model




Variance σ^2

amplitude of variations



Texture's attributes definition

Piecewise monofractal model




Variance σ^2 *amplitude of variations*


Local regularity h *scale-free behavior*



$$h(x) \equiv h_1 = 0.9$$



$$h(x) \equiv h_2 = 0.3$$




Fit local behavior with power law functions

$$|f(x) - f(y)| \leq C|x - y|^{h(x)}$$



Texture's attributes definition

Piecewise monofractal model



Variance σ^2 *amplitude of variations*

Local regularity h *scale-free behavior*



$h(x) \equiv h_1 = 0.9$ $h(x) \equiv h_2 = 0.3$

Fit local behavior with power law functions


$$|f(x) - f(y)| \leq C|x - y|^{h(x)}$$

Segmentation requires local measurement of σ^2 and h .

Texture's attributes estimation

Multiscale analysis


Textured image




Texture's attributes estimation

Multiscale analysis

Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$



scale a



Texture's attributes estimation

Multiscale analysis




Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$.

Scale


$a = 2^1$

$a = 2^2$


$a = 2^5$



...



scale a



Texture's attributes estimation

Multiscale analysis




Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$.

Scale


$a = 2^1$

$a = 2^2$

$a = 2^5$



...



Log-log linear behavior


$$\log(\mathcal{L}_{a,\cdot}) \simeq \underbrace{\underline{v}}_{\sim \log(\sigma^2)} + \log(a) \underbrace{\underline{h}}_{\text{regularity}}$$

(variance)

Texture's attributes estimation

Multiscale analysis

Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$.





Scale


$a = 2^1$

$a = 2^2$

$a = 2^5$




...



Log-log linear behavior

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{v}{\sim \log(\sigma^2)} + \log(a) \frac{h}{\text{regularity}}$$


(variance)



Texture's attributes estimation


Multiscale analysis

Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$.




Scale

$a = 2^1$




$a = 2^2$



$a = 2^5$


...



Log-log linear behavior

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{v}{\sim \log(\sigma^2)} + \log(a) \frac{h}{\text{regularity}}$$


(variance)



Texture's attributes estimation


Multiscale analysis

Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$.




Scale

$a = 2^1$




$a = 2^2$



$a = 2^5$


...



Log-log linear behavior

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{v}{\sim \log(\sigma^2)} + \log(a) \frac{h}{\text{regularity}}$$


(variance)



Texture's attributes estimation

Multiscale analysis


Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$.



Log-log linear behavior

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{v}{\sim \log(\sigma^2)} + \log(a) \frac{h}{\text{regularity}}$$


(variance)



Texture's attributes estimation

Multiscale analysis

Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$.





Scale


$a = 2^1$

$a = 2^2$

$a = 2^5$




...



Log-log linear behavior

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{v}{\sim \log(\sigma^2)} + \log(a) \frac{h}{\text{regularity}}$$


(variance)



Texture's attributes estimation

Multiscale analysis


Textured image Local supremum of wavelet coefficients: *leaders* $\mathcal{L}_{a,\cdot}$,



Log-log linear behavior

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{v}{\sim \log(\sigma^2)} + \log(a) \frac{h}{\text{regularity}}$$

(variance)



Texture's attributes estimation

Pointwise linear regression

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{\underline{v}}{\sim \log(\sigma^2)} + \log(a) \frac{\underline{h}}{regularity}$$


Texture's attributes estimation

Pointwise linear regression

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{\mathbf{v}}{\sim \log(\sigma^2)} + \log(a) \frac{\mathbf{h}}{regularity}$$

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \sum_a \|\log(\mathcal{L}_{a,\cdot}) - \mathbf{v} - \log(a)\mathbf{h}\|^2$$

Textured image



Texture's attributes estimation




Pointwise linear regression

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{\mathbf{v}}{\sim \log(\sigma^2)} + \log(a) \frac{\mathbf{h}}{\text{regularity}}$$

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \sum_a \|\log(\mathcal{L}_{a,\cdot}) - \mathbf{v} - \log(a)\mathbf{h}\|^2$$

Local power $\widehat{\mathbf{v}}^{\text{LR}}$ Local regularity $\widehat{\mathbf{h}}^{\text{LR}}$

Textured image





Texture's attributes estimation

Pointwise linear regression


$$\frac{\mathbb{E} \log(\mathcal{L}_{a,\cdot})}{\text{expected value}} \simeq \frac{\mathbf{v}}{\sim \log(\sigma^2)} + \log(a) \frac{\mathbf{h}}{\text{regularity}}$$

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \sum_a \|\log(\mathcal{L}_{a,\cdot}) - \mathbf{v} - \log(a)\mathbf{h}\|^2$$

Textured image



Local power $\hat{\mathbf{v}}^{\text{LR}}$



Pointwise linear regression is an estimation from one sample!

Outline – Fractal texture segmentation

1. Fractal texture model

$$\log(\mathcal{L}_{a,\cdot}) \simeq \frac{\nu}{\sim \log(\sigma^2)} + \log(a) \frac{h}{regularity}$$

2. Attributes estimation and segmentation

3. Multiphasic flow segmentation


4. Regularization parameters tuning

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}}$$

→ fidelity to log-linear model




Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy




Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} \quad + \quad \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy




Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} \quad + \quad \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy



joint: \mathbf{v} , \mathbf{h} are **independently** piecewise constant


coupled: \mathbf{v} , \mathbf{h} are **concomitantly** piecewise constant

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy



Discrete differences \mathbf{Hx} (horizontal), \mathbf{Vx} (vertical) at each pixel

joint: \mathbf{v} , \mathbf{h} are **independently** piecewise constant

$$\mathcal{N}_J(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha) = \left(\sum_{\text{pixels}} \sqrt{(\mathbf{Hv})^2 + (\mathbf{Vv})^2} + \alpha \sum_{\text{pixels}} \sqrt{(\mathbf{Hh})^2 + (\mathbf{Vh})^2} \right)$$

coupled: \mathbf{v} , \mathbf{h} are **concomitantly** piecewise constant


$$\mathcal{N}_C(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha) = \sum_{\text{pixels}} \sqrt{(\mathbf{Hv})^2 + (\mathbf{Vv})^2 + \alpha^2(\mathbf{Hh})^2 + \alpha^2(\mathbf{Vh})^2}$$

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} \quad + \quad \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy



Discrete differences $\mathbf{D}\mathbf{x} = [\mathbf{H}\mathbf{x}, \mathbf{V}\mathbf{x}]$

joint: \mathbf{v} , \mathbf{h} are **independently** piecewise constant

$$\mathcal{N}_J(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha) = \|\mathbf{D}\mathbf{v}\|_{2,1} + \alpha \|\mathbf{D}\mathbf{h}\|_{2,1}$$

coupled: \mathbf{v} , \mathbf{h} are **concomitantly** piecewise constant

$$\mathcal{N}_C(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha) = \|[\mathbf{D}\mathbf{v}, \alpha \mathbf{D}\mathbf{h}]\|_{2,1}$$

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization


$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$



Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$




μ -strongly convex

convex

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$



μ -strongly convex


convex

φ is μ -strongly convex iff $\varphi - \frac{\mu}{2} \|\cdot\|^2$ is convex.


Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$




φ is μ -strongly convex iff $\varphi - \frac{\mu}{2} \|\cdot\|^2$ is convex.



Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$



μ -strongly convex

convex


φ is μ -strongly convex iff $\varphi - \frac{\mu}{2} \|\cdot\|^2$ is convex.

If φ is \mathcal{C}^2 with Hessian $\mathbf{H}\varphi$, φ is $\min \text{Sp}(\mathbf{H}\varphi)$ -strongly convex.

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$



φ is μ -strongly convex iff $\varphi - \frac{\mu}{2}\|\cdot\|^2$ is convex.

If φ is \mathcal{C}^2 with Hessian $\mathbf{H}\varphi$, φ is $\min \text{Sp}(\mathbf{H}\varphi)$ -strongly convex.

$$\text{LS}(\boldsymbol{v}, \boldsymbol{h}) = \sum_{a=a_{\min}}^{a_{\max}} \|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2 = \|\log \mathcal{L} - \mathbf{A}(\boldsymbol{v}, \boldsymbol{h})\|^2$$


$$\mathbf{H}\text{LS} = 2\mathbf{A}^*\mathbf{A}, \quad \text{with} \quad \mathbf{A} : (\boldsymbol{v}, \boldsymbol{h}) \mapsto \{\boldsymbol{v} + \log(a)\boldsymbol{h}\}_{a=a_{\min}}^{a_{\max}}$$

$\text{LS}(\boldsymbol{v}, \boldsymbol{h})$ is μ -strongly convex, μ the smallest eigenvalue of $2\mathbf{A}^*\mathbf{A}$

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization


$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$



Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$



μ -strongly convex




nonsmooth



Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$



μ -strongly convex



Accelerated primal-dual algorithm (Chambolle, Pock 11')

$$\mathbf{x}^n = (\boldsymbol{v}^n, \boldsymbol{h}^n), \quad \mathbf{y}^n = (\boldsymbol{u}^n, \ell^n)$$

$$\mathbf{y}^{n+1} = \text{prox}_{\sigma_n \|\cdot\|_{2,1}} (\mathbf{y}^n + \sigma_n \mathbf{D} \bar{\mathbf{x}}^n)$$

$$\mathbf{x}^{n+1} = \text{prox}_{\tau_n \text{LS}} (\mathbf{x}^n - \tau_n \mathbf{D}^* \mathbf{y}^{n+1})$$


$$\theta_n = \sqrt{1 + 2\mu\tau_n}, \quad \tau_{n+1} = \tau_n / \theta_n, \quad \sigma_{n+1} = \theta_n \sigma_n$$

$$\bar{\mathbf{x}}^{n+1} = \mathbf{x}^{n+1} + \theta_n^{-1} (\mathbf{x}^{n+1} - \mathbf{x}^n)$$

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$



μ -strongly convex



nonsmooth



Accelerated primal-dual algorithm (Chambolle, Pock 11')


$$\mathbf{x}^n = (\mathbf{v}^n, \mathbf{h}^n), \quad \mathbf{y}^n = (\mathbf{u}^n, \ell^n)$$

$$\delta(\mathbf{x}^n; \mathbf{y}^n) = \text{LS}(\mathbf{x}^n) + \mathcal{N}(\mathbf{D}\mathbf{x}^n) - (-\text{LS}^*(-\mathbf{D}^*\mathbf{y}^n) - \mathcal{N}^*(\mathbf{y}^n)) \xrightarrow{n \rightarrow \infty} 0$$

Texture's attributes estimation

One-step joint and coupled segmentation as a convex minimization


$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$



Accelerated primal-dual algorithm (Chambolle, Pock 11')

$$\mathbf{x}^n = (\mathbf{v}^n, \mathbf{h}^n), \quad \mathbf{y}^n = (\mathbf{u}^n, \ell^n)$$

$$\delta(\mathbf{x}^n; \mathbf{y}^n) = \text{LS}(\mathbf{x}^n) + \mathcal{N}(\mathbf{D}\mathbf{x}^n) - (-\text{LS}^*(-\mathbf{D}^*\mathbf{y}^n) - \mathcal{N}^*(\mathbf{y}^n)) \xrightarrow[n \rightarrow \infty]{} 0$$




Texture's attributes estimation

Iterated thresholding for segmentation

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$

Textured image





Texture's attributes estimation

Iterated thresholding for segmentation

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} \quad + \quad \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

Textured image Lin. Reg. $\hat{\boldsymbol{h}}^{\text{LR}}$




Texture's attributes estimation

Iterated thresholding for segmentation

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$


Textured image



Lin. Reg. $\hat{\boldsymbol{h}}^{\text{LR}}$




Coupled $\hat{\boldsymbol{h}}^{\text{C}}$



Texture's attributes estimation

Iterated thresholding for segmentation

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$




X.Cai, et al., *Multiclass segmentation by iterated ROF thresholding* (2013)

State-of-the-art two-step texture segmentation

Factorization-based segmentation [Yuan et al. 15'][†]

(i) local spectral histograms



(ii) matrix factorization





Fig. 2. Scatterplot of features in subspace. (a) Scatterplot of features projected onto the 3-d subspace. (b) Scatterplot after removing features with high edgehood.

[†]<https://sites.google.com/site/factorizationsegmentation/>

State-of-the-art two-step texture segmentation

Factorization-based segmentation [Yuan et al. 15'][†]

(i) local spectral histograms



(ii) matrix factorization




Fig. 2. Scatterplot of features in subspace. (a) Scatterplot of features projected onto the 3-d subspace. (b) Scatterplot after removing features with high edgehood.


Threshold-ROF on $\hat{\mathbf{h}}^{\text{LR}}$ [Pustelnik 16']

$$\min_{\mathbf{h}} \|\mathbf{h} - \hat{\mathbf{h}}^{\text{LR}}\|^2 + \lambda \|\mathbf{D}\mathbf{h}\|_{2,1}$$

Lin. Reg.



ROF



Threshold



Based on regularity \mathbf{h} only.

[†]<https://sites.google.com/site/factorizationsegmentation/>

Outline – Fractal texture segmentation

1. Fractal texture model

$$\log(\mathcal{L}_{a,\cdot}) \simeq \underset{\sim \log(\sigma^2)}{\underline{\boldsymbol{v}}} + \log(a) \underset{\text{regularity}}{\underline{\boldsymbol{h}}}$$

2. Attributes estimation and segmentation


$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \sum_a \frac{\|\log \mathcal{L}_{a,\cdot} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

3. Multiphasic flow segmentation

4. Regularization parameters tuning


Multiphasic (quasi 2D) flow in a porous media

Laboratoire de Physique, ENS Lyon, V. Vidal, T. Busser, (M. Serres, IFPEN)




Multiphasic (quasi 2D) flow in a porous media

Laboratoire de Physique, ENS Lyon, V. Vidal, T. Busser, (M. Serres, IFPEN)




Multiphase (quasi 2D) flow in a porous media

Laboratoire de Physique, ENS Lyon, V. Vidal, T. Busser, (M. Serres, IFPEN)




Normalized image




Textured

Multiphasic (quasi 2D) flow in a porous media

Laboratoire de Physique, ENS Lyon, V. Vidal, T. Busser, (M. Serres, IFPEN)




Normalized image





Textured

Physical quantities: gas volume & contact surface.




Texture segmentation



Texture segmentation



Texture segmentation




Purpose: obtaining a partition of the image into two regions


$$\Omega = \Omega_1 \sqcup \Omega_2$$

Ω_1 : liquid, Ω_2 : gas.

Multiphasic flow. $Q_G = 300\text{mL/min}$ - $Q_L = 300\text{mL/min}$: low activity




Multiphasic flow. $Q_G = 300\text{mL/min}$ - $Q_L = 300\text{mL/min}$: low activity



Liquid: $h_L = 0.4$

Gas: $h_G = 0.9$

Multiphasic flow. $Q_G = 300\text{mL/min}$ - $Q_L = 300\text{mL/min}$: low activity




$$\text{Liquid: } h_L = 0.4$$

$$\text{Gas: } h_G = 0.9$$

$$\sigma_{\text{dark}}^2 = 10^{-2}$$

$$\sigma_{\text{dark}}^2 = 10^{-2} \text{(dark bubbles)}$$

Multiphasic flow. $Q_G = 300\text{mL/min}$ - $Q_L = 300\text{mL/min}$: low activity




Liquid: $h_L = 0.4$

Gas: $h_G = 0.9$

$$\left| \begin{array}{l} \sigma_{\text{dark}}^2 = 10^{-2} \\ \sigma_{\text{dark}}^2 = 10^{-2} \text{(dark bubbles)} \\ \sigma_{\text{clear}}^2 = 10^{-1} \text{(clear bubbles)} \end{array} \right.$$

Multiphasic flow. $Q_G = 400\text{mL/min}$ - $Q_L = 700\text{mL/min}$: transition




Liquid: $h_L = 0.4$

Gas: $h_G = 0.9$

$$\left| \begin{array}{l} \sigma_{\text{dark}}^2 = 10^{-2} \\ \sigma_{\text{dark}}^2 = 10^{-2} (\text{dark bubbles}) \\ \sigma_{\text{clear}}^2 = 10^{-1} (\text{clear bubbles}) \end{array} \right.$$

Multiphasic flow. $Q_G = 1200\text{mL/min}$ - $Q_L = 300\text{mL/min}$: high activity




Liquid: $h_L = 0.4$

Gas: $h_G = 0.9$

$$\left| \begin{array}{l} \sigma_{\text{dark}}^2 = 10^{-2} \\ \sigma_{\text{dark}}^2 = 10^{-2} (\text{dark bubbles}) \\ \sigma_{\text{clear}}^2 = 10^{-1} (\text{clear bubbles}) \end{array} \right.$$

Multiphasic flow. $Q_G = 1200\text{mL/min}$ - $Q_L = 300\text{mL/min}$: high activity



Liquid: $h_L = 0.4$

Gas: $h_G = 0.9$

$$\left| \begin{array}{l} \sigma_{\text{dark}}^2 = 10^{-2} \\ \sigma_{\text{dark}}^2 = 10^{-2} \text{(dark bubbles)} \\ \sigma_{\text{clear}}^2 = 10^{-1} \text{(clear bubbles)} \end{array} \right.$$

Outline – Fractal texture segmentation

1. Fractal texture model

$$\log(\mathcal{L}_{a,\cdot}) \simeq \underset{\sim \log(\sigma^2)}{\underline{\boldsymbol{v}}} + \log(a) \underset{regularity}{\underline{\boldsymbol{h}}}$$

2. Attributes estimation and segmentation

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \sum_a \frac{\|\log \mathcal{L}_{a,\cdot} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

3. Multiphasic flow segmentation



4. Regularization parameters tuning

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

Lin. Reg. $\hat{\boldsymbol{h}}^{\text{LR}}$




Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

Lin. Reg. $\hat{\boldsymbol{h}}^{\text{LR}}$

Too small



Texture's attributes estimation


Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

Lin. Reg. $\hat{\boldsymbol{h}}^{\text{LR}}$



Too small



Too large



Texture's attributes estimation


Hyperparameters tuning

$$\underset{\mathbf{v}, \mathbf{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}; \alpha)}{\text{Total Variation}}$$


Lin. Reg. $\hat{\mathbf{h}}^{\text{LR}}$




Too small



Optimal



Too large



Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} \quad + \quad \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$\bar{\boldsymbol{h}}$: true regularity

$$\mathcal{R}(\lambda, \alpha) = \left\| \hat{\boldsymbol{h}}_{\lambda, \alpha} - \bar{\boldsymbol{h}} \right\|^2$$


Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$\bar{\boldsymbol{h}}$: true regularity

$$\mathcal{R}(\lambda, \alpha) = \left\| \hat{\boldsymbol{h}}_{\lambda, \alpha} - \bar{\boldsymbol{h}} \right\|^2$$




Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$\bar{\boldsymbol{h}}$: true regularity

$$\mathcal{R}(\lambda, \alpha) = \left\| \hat{\boldsymbol{h}}_{\lambda, \alpha} - \bar{\boldsymbol{h}} \right\|^2$$



Texture's attributes estimation

Hyperparameters tuning


$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$\bar{\boldsymbol{h}}$: true regularity

$\bar{\boldsymbol{h}}$: unknown!

$$\mathcal{R}(\lambda, \alpha) = \left\| \hat{\boldsymbol{h}}_{\lambda, \alpha} - \bar{\boldsymbol{h}} \right\|^2$$

?



Texture's attributes estimation

Hyperparameters tuning


$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$\bar{\boldsymbol{h}}$: true regularity

$$\mathcal{R}(\lambda, \alpha) = \left\| \widehat{\boldsymbol{h}}_{\lambda, \alpha} - \bar{\boldsymbol{h}} \right\|^2$$

$\bar{\boldsymbol{h}}$: unknown!

?



Stein Unbiased Risk Estimate

$$\mathbb{E}[\widehat{\mathcal{R}}(\lambda, \alpha)] = \mathcal{R}(\lambda, \alpha)$$

ind. of $\bar{\boldsymbol{h}}$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

$$\text{Observation model} \quad \mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N, \quad \text{Estimator} \quad \hat{\mathbf{x}}(\mathbf{y}; \lambda)$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

Observation model $\mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N$, Estimator $\hat{\mathbf{x}}(\mathbf{y}; \lambda)$

- If \boldsymbol{n} is i.i.d. Gaussian noise of variance ρ^2

$$R(\lambda) \triangleq \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \bar{\mathbf{x}}\|^2$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

$$\text{Observation model} \quad \mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N, \quad \text{Estimator} \quad \hat{\mathbf{x}}(\mathbf{y}; \lambda)$$

- If \boldsymbol{n} is i.i.d. Gaussian noise of variance ρ^2

$$R(\lambda) \triangleq \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \bar{\mathbf{x}}\|^2 = \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y} + \mathbf{y} - \bar{\mathbf{x}}\|^2$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

Observation model $\mathbf{y} = \bar{\mathbf{x}}_{\text{truth}} + \mathbf{n}_{\text{noise}} \in \mathbb{R}^N$, Estimator $\hat{\mathbf{x}}(\mathbf{y}; \lambda)$

- If \mathbf{n} is i.i.d. Gaussian noise of variance ρ^2

$$\begin{aligned} R(\lambda) &\triangleq \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \bar{\mathbf{x}}\|^2 = \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y} + \mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}, \mathbf{y} - \bar{\mathbf{x}} \rangle + \mathbb{E} \|\mathbf{y} - \bar{\mathbf{x}}\|^2 \end{aligned}$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

$$\text{Observation model} \quad \mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N, \quad \text{Estimator} \quad \hat{\mathbf{x}}(\mathbf{y}; \lambda)$$

- If \boldsymbol{n} is i.i.d. Gaussian noise of variance ρ^2

$$\begin{aligned} R(\lambda) &\triangleq \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \bar{\mathbf{x}}\|^2 = \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y} + \mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}, \mathbf{y} - \bar{\mathbf{x}} \rangle + \mathbb{E} \|\mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2 \underbrace{\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda), \boldsymbol{n} \rangle}_{-\mathbb{E} \|\boldsymbol{n}\|^2} \end{aligned}$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

$$\text{Observation model} \quad \mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N, \quad \text{Estimator} \quad \hat{\mathbf{x}}(\mathbf{y}; \lambda)$$

- If \boldsymbol{n} is i.i.d. Gaussian noise of variance ρ^2

$$\begin{aligned} R(\lambda) &\triangleq \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \bar{\mathbf{x}}\|^2 = \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y} + \mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}, \mathbf{y} - \bar{\mathbf{x}} \rangle + \mathbb{E} \|\mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \underbrace{\mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2}_{\text{known}} + 2 \underbrace{\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda), \boldsymbol{n} \rangle}_{-} - \underbrace{\mathbb{E} \|\boldsymbol{n}\|^2}_{-} \end{aligned}$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

Observation model $\mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N$, Estimator $\hat{\mathbf{x}}(\mathbf{y}; \lambda)$

- If \boldsymbol{n} is i.i.d. Gaussian noise of variance ρ^2

$$\begin{aligned} R(\lambda) &\triangleq \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \bar{\mathbf{x}}\|^2 = \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y} + \mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}, \mathbf{y} - \bar{\mathbf{x}} \rangle + \mathbb{E} \|\mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \underbrace{\mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2}_{\text{known}} + 2 \underbrace{\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda), \boldsymbol{n} \rangle}_{-\frac{\mathbb{E} \|\boldsymbol{n}\|^2}{\rho^2 N}} \end{aligned}$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

$$\text{Observation model} \quad \mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N, \quad \text{Estimator} \quad \hat{\mathbf{x}}(\mathbf{y}; \lambda)$$

- If \boldsymbol{n} is i.i.d. Gaussian noise of variance ρ^2

$$\begin{aligned} R(\lambda) &\triangleq \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \bar{\mathbf{x}}\|^2 = \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y} + \mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}, \mathbf{y} - \bar{\mathbf{x}} \rangle + \mathbb{E} \|\mathbf{y} - \bar{\mathbf{x}}\|^2 \\ &= \underbrace{\mathbb{E} \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2}_{\text{known}} + 2 \underbrace{\frac{\mathbb{E} \langle \hat{\mathbf{x}}(\mathbf{y}; \lambda), \boldsymbol{n} \rangle}{\int \hat{\mathbf{x}}(\boldsymbol{n}) \boldsymbol{n} \exp(-\|\boldsymbol{n}\|^2/2\rho^2)}} - \frac{\mathbb{E} \|\boldsymbol{n}\|^2}{\rho^2 N} \end{aligned}$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

Observation model $\mathbf{y} = \bar{\mathbf{x}}_{\text{truth}} + \mathbf{n}_{\text{noise}} \in \mathbb{R}^N$, Estimator $\hat{\mathbf{x}}(\mathbf{y}; \lambda)$

- If \mathbf{n} is i.i.d. Gaussian noise of variance ρ^2

$$\hat{R}(\lambda|\rho^2) \triangleq \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2\text{tr} \left(\frac{\partial \hat{\mathbf{x}}}{\partial \mathbf{y}}(\mathbf{y}; \lambda) \right) - \rho^2 N$$

Texture's attributes estimation

Hyperparameters tuning

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \frac{\lambda \mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

$$\text{Fractal model} \quad \log \mathcal{L}_{a,.} = \bar{\boldsymbol{v}} + \log(a)\bar{\boldsymbol{h}} + \boldsymbol{\varepsilon}_{a,.}$$

Stein Unbiased Risk Estimator (SURE) $\hat{R}(\lambda)$

$$\text{Observation model} \quad \mathbf{y} = \underbrace{\bar{\mathbf{x}}}_{\text{truth}} + \underbrace{\boldsymbol{n}}_{\text{noise}} \in \mathbb{R}^N, \quad \text{Estimator} \quad \hat{\mathbf{x}}(\mathbf{y}; \lambda)$$

- If \boldsymbol{n} is i.i.d. Gaussian noise of variance ρ^2

$$\hat{R}(\lambda|\rho^2) \triangleq \|\hat{\mathbf{x}}(\mathbf{y}; \lambda) - \mathbf{y}\|^2 + 2\text{tr} \left(\frac{\partial \hat{\mathbf{x}}}{\partial \mathbf{y}}(\mathbf{y}; \lambda) \right) - \rho^2 N$$

- Fractal model: $\boldsymbol{\varepsilon}$ Gaussian with covariance matrix \mathcal{S}

$$\hat{R}(\lambda|\mathcal{S}) \quad \nabla_\lambda \hat{R}(\lambda|\mathcal{S})$$



Thank you for your attention!

Outline – Fractal texture segmentation

1. Fractal texture model

$$\log(\mathcal{L}_{a,\cdot}) \simeq \underset{\sim \log(\sigma^2)}{\underline{\boldsymbol{v}}} + \log(a) \underset{regularity}{\underline{\boldsymbol{h}}}$$

2. Attributes estimation and segmentation

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \sum_a \frac{\|\log \mathcal{L}_{a,\cdot} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \lambda \frac{\mathcal{N}(\mathbf{D}\boldsymbol{v}, \mathbf{D}\boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

3. Multiphasic flow segmentation




4. Regularization parameters tuning

Texture's attributes estimation

Fine tuning of regularization parameters

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} \quad + \quad \frac{\lambda \mathcal{N}(\boldsymbol{v}, \boldsymbol{h}; \boldsymbol{\alpha})}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy




Texture's attributes estimation



Fine tuning of regularization parameters

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} \quad + \quad \frac{\lambda \mathcal{N}(\boldsymbol{v}, \boldsymbol{h}; \boldsymbol{\alpha})}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy



Fine tuning of regularization parameters (λ, α) is necessary ...




Texture's attributes estimation


Fine tuning of regularization parameters

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \quad \sum_a \frac{\|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a)\boldsymbol{h}\|^2}{\text{Least-Squares}} + \frac{\lambda \mathcal{N}(\boldsymbol{v}, \boldsymbol{h}; \alpha)}{\text{Total Variation}}$$

\rightarrow fidelity to log-linear model \rightarrow enforce piecewise constancy



Fine tuning of regularization parameters (λ, α) is necessary . . . but **costly!**



In practice, we explore a log-spaced grid of $15 \times 15 = 225$ hyperparameters (λ, α) .

Ongoing work and perspectives

- Video analysis (temporal series of hundreds of images)

Intership of L. Helmlinger

Ongoing work and perspectives

- Video analysis (temporal series of hundreds of images)

Intership of L. Helmlinger

- ✓ Best (λ, α) tuned on 1st image is sufficiently robust for the entire series.


Ongoing work and perspectives

- Video analysis (temporal series of hundreds of images)


Internship of L. Helmlinger

- ✓ Best (λ, α) tuned on 1st image is sufficiently robust for the entire series.
- ✓ Time evolution of physical quantities can be assessed.

Fraction of gas (area)



Liquid/gas contact perimeter





Ongoing work and perspectives

- Video analysis (temporal series of hundreds of images)

Intership of L. Helmlinger

- ✓ Best (λ, α) tuned on 1st image is sufficiently robust for the entire series.
- ✓ Time evolution of physical quantities can be assessed.




- Automatic tuning of hyperparameters

Stein's Unbiased Risk Estimate $\widehat{\mathcal{R}}(\lambda, \alpha)$


Stein Unbiased GrAdient estimator of the Risk $\nabla_{\lambda} \widehat{\mathcal{R}}(\lambda, \alpha)$

Fully Convolutional Neural Networks[†]



[†] V. Andriarczyk, <https://arxiv.org/abs/1703.05230>

Fully Convolutional Neural Networks[†]




[†] V. Andriarczyk, <https://arxiv.org/abs/1703.05230>

Gas/liquid flow modeled by piecewise monofractal textures

Synthetic textures

Liquid: $h_1 = 0.4, \sigma_1^2 = 10^{-2}$

Mask



Texture



Gas/liquid flow modeled by piecewise monofractal textures


Synthetic textures

Liquid: $h_1 = 0.4, \sigma_1^2 = 10^{-2}$
Gas: $h_2 = 0.9, \sigma_1^2 = 10^{-2}$ (dark bubbles)

Mask



Texture



Gas/liquid flow modeled by piecewise monofractal textures

Synthetic textures


Liquid: $h_1 = 0.4, \sigma_1^2 = 10^{-2}$

Gas: $h_2 = 0.9, \sigma_1^2 = 10^{-2}$ (dark bubbles)
 $h_2 = 0.9, \sigma_2^2 = 10^{-1}$ (clear bubbles)

Mask



Texture



Gas/liquid flow modeled by piecewise monofractal textures


Synthetic textures

Liquid: $h_1 = 0.4, \sigma_1^2 = 10^{-2}$
Gas: $h_2 = 0.9, \sigma_1^2 = 10^{-2}$ (dark bubbles)
 $h_2 = 0.9, \sigma_2^2 = 10^{-1}$ (clear bubbles)

Mask




Texture




Segmentation performance


'Gas/Liquid'




Yuan 88%




T-ROF 88%



Joint 95%



Coupled 95%




Optimization scheme - Monofractal model and piecewise constancy

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \sum_a \|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a) \boldsymbol{h}\|^2 + \lambda \mathcal{N}(\boldsymbol{v}, \boldsymbol{h}; \alpha)$$

Optimization scheme - Monofractal model and piecewise constancy

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \sum_a \|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a) \boldsymbol{h}\|^2 + \lambda \mathcal{N}(\boldsymbol{v}, \boldsymbol{h}; \alpha)$$

aim: enforce piecewise behavior of estimate




Discrete difference operator


$$(\mathbf{D}\mathbf{x})_{n_1, n_2} := \begin{pmatrix} x_{n_1, n_2+1} - x_{n_1, n_2} \\ x_{n_1+1, n_2} - x_{n_1, n_2} \end{pmatrix} := \begin{bmatrix} \mathbf{H}\mathbf{x} \\ \mathbf{V}\mathbf{x} \end{bmatrix}_{n_1, n_2}$$

Total Variation penalization


$$\mathcal{N}(\mathbf{x}) = \|\mathbf{D}\mathbf{x}\|_{2,1} = \sum_{n_1=1}^{N-1} \sum_{n_2=1}^{N-1} \sqrt{(\mathbf{H}\mathbf{x})_{n_1, n_2}^2 + (\mathbf{V}\mathbf{x})_{n_1, n_2}^2}$$



Too small



Optimal



Too large

Optimization scheme - Monofractal model and piecewise constancy

$$\underset{\boldsymbol{v}, \boldsymbol{h}}{\text{minimize}} \sum_a \|\log \mathcal{L}_{a,.} - \boldsymbol{v} - \log(a) \boldsymbol{h}\|^2 + \lambda \mathcal{N}(\boldsymbol{v}, \boldsymbol{h}; \alpha)$$


State-of-the-art - Segmentation on \boldsymbol{h} only

$$\underset{\boldsymbol{h}}{\text{minimize}} \|\boldsymbol{h} - \hat{\boldsymbol{h}}^{\text{LR}}\|_2^2 + \lambda \mathcal{N}(\boldsymbol{h})$$

$$\underset{\boldsymbol{h}, \boldsymbol{\omega}}{\text{minimize}} \|\boldsymbol{h} - \sum_a \boldsymbol{\omega}_a \mathcal{L}_{a,.}\|_2^2 + \lambda \mathcal{N}(\boldsymbol{h}, \boldsymbol{\omega}; \alpha_a)$$

- ✓ only one parameter λ
- ✓ fast algorithms [Pascal2018]

- ✗ additional constraints on $\{\boldsymbol{\omega}\}_a$
- ✗ time and memory consuming



✗ poor segmentation performance

✓ very good accuracy [Pustelnik2016]


Strong convexity of data fidelity term

$$\text{LS}(\mathbf{v}, \mathbf{h}) = \sum_{a=a_{\min}}^{a_{\max}} \|\log \mathcal{L}_{a,.} - \mathbf{v} - \log(a)\mathbf{h}\|^2 = \|\log \mathcal{L} - \mathbf{A}(\mathbf{v}, \mathbf{h})\|^2$$

where $\mathbf{A} : (\mathbf{v}, \mathbf{h}) \mapsto \{\mathbf{v} + \log(a)\mathbf{h}\}_{a=a_{\min}}^{a_{\max}}$ is linear.

$$\mathbf{HLS}(\mathbf{v}, \mathbf{h}) = \mathbf{A}^* \mathbf{A} = \begin{pmatrix} \mathbf{A}_0 \mathbf{I} & \mathbf{A}_1 \mathbf{I} \\ \mathbf{A}_1 \mathbf{I} & \mathbf{A}_2 \mathbf{I} \end{pmatrix}, \quad \mathbf{A}_m = \sum_{a=a_{\min}}^{a_{\max}} (\log a)^m, \quad \forall m \in \{0, 1, 2\}.$$

Prop: $\text{LS}(\mathbf{v}, \mathbf{h})$ is μ -strongly convex, μ the smallest eigenvalue of $\mathbf{A}^* \mathbf{A}$.




Convergence speed and stopping criterion

Duality gap

Primal problem

$$\hat{x} = \underset{x}{\operatorname{argmin}} \text{ LS}(x) + \mathcal{N}(\mathbf{D}x)$$



Convergence speed and stopping criterion


Duality gap

Primal problem

$$\hat{x} = \underset{x}{\operatorname{argmin}} \text{LS}(x) + \mathcal{N}(\mathbf{D}x)$$

Dual problem

$$\hat{y} = \underset{y}{\operatorname{argmax}} -\text{LS}^*(-\mathbf{D}^*y) - \mathcal{N}^*(y)$$



Convergence speed and stopping criterion

Duality gap

Primal problem


$$\hat{x} = \underset{x}{\operatorname{argmin}} \text{LS}(x) + \mathcal{N}(\mathbf{D}x)$$

Dual problem

$$\hat{y} = \underset{y}{\operatorname{argmax}} -\text{LS}^*(-\mathbf{D}^*y) - \mathcal{N}^*(y)$$

Duality gap $\delta(x; y)$

$$= \underset{\text{def.}}{\text{LS}(x) + \mathcal{N}(\mathbf{D}x) + \text{LS}^*(-\mathbf{D}^*y) + \mathcal{N}^*(y)}$$



Convergence speed and stopping criterion

Duality gap

Primal problem

$$\hat{x} = \underset{x}{\operatorname{argmin}} \text{LS}(x) + \mathcal{N}(\mathbf{D}x)$$

Dual problem


$$\hat{y} = \underset{y}{\operatorname{argmax}} -\text{LS}^*(-\mathbf{D}^*y) - \mathcal{N}^*(y)$$

Duality gap $\delta(x; y)$

$$= \underset{\text{def.}}{\text{LS}(x) + \mathcal{N}(\mathbf{D}x) + \text{LS}^*(-\mathbf{D}^*y) + \mathcal{N}^*(y)}$$

Characterization of the solution

$$\delta(\hat{x}; \hat{y}) \underset{\text{prop.}}{=} 0$$



Computing the duality gap

For Joint penalization

$$\delta(\quad; \quad)$$

$$= +$$

Computing the duality gap

For Joint penalization

$$\delta(\mathbf{v}, \mathbf{h}; \quad)_{\text{primal}} \\ = \text{LS}(\mathbf{v}, \mathbf{h}) + \mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}) +$$

Data fidelity

$$\text{LS}(\mathbf{v}, \mathbf{h}) = \sum_a \|\mathbf{v} + \log(a)\mathbf{h} - \mathcal{L}_{a,.}\|_2^2$$

Penalization

$$\mathcal{N}(\mathbf{u}, \ell) = \lambda (\|\mathbf{u}\|_{2,1} + \alpha \|\ell\|_{2,1})$$

Computing the duality gap

For Joint penalization

$$\begin{aligned} & \delta_{\text{primal dual}}(\mathbf{v}, \mathbf{h}; \mathbf{u}, \boldsymbol{\ell}) \\ = & \text{LS}(\mathbf{v}, \mathbf{h}) + \mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}) + \text{LS}^*(-\mathbf{D}^*\mathbf{u}, -\mathbf{D}^*\boldsymbol{\ell}) + \mathcal{N}^*(\mathbf{u}, \boldsymbol{\ell}) \end{aligned}$$

Data fidelity

$$\text{LS}(\mathbf{v}, \mathbf{h}) = \sum_a \|\mathbf{v} + \log(a)\mathbf{h} - \mathcal{L}_{a,.}\|_2^2$$

Penalization

$$\mathcal{N}(\mathbf{u}, \boldsymbol{\ell}) = \lambda (\|\mathbf{u}\|_{2,1} + \alpha \|\boldsymbol{\ell}\|_{2,1})$$

$$\text{LS}^*(\mathbf{v}, \mathbf{h})$$

$$= \frac{1}{4} \langle (\mathbf{v}, \mathbf{h}), (\mathbf{A}^* \mathbf{A})^{-1}(\mathbf{v}, \mathbf{h}) \rangle$$

$$\mathcal{N}^*(\mathbf{u}, \boldsymbol{\ell}) = \iota_{B_{2,\infty}(\lambda)}(\mathbf{u}) + \iota_{B_{2,\infty}(\lambda\alpha)}(\boldsymbol{\ell})$$

$B_{2,\infty}(\lambda)$: ball of radius λ w.r.t. $\|\cdot\|_{2,\infty}$.

$$+ \langle (\mathcal{S}, \mathcal{T}), (\mathbf{A}^* \mathbf{A})^{-1}(\mathbf{v}, \mathbf{h}) \rangle$$


$$+ \mathcal{C}$$

where \mathcal{C} constant term only
depending on $\mathcal{L}_{a,.}$

Computing the duality gap

For Joint penalization

$$\begin{aligned} & \delta(\mathbf{v}, \mathbf{h}; \mathbf{u}, \boldsymbol{\ell}) \\ & \quad \text{primal} \quad \text{dual} \\ = & \text{LS}(\mathbf{v}, \mathbf{h}) + \mathcal{N}(\mathbf{D}\mathbf{v}, \mathbf{D}\mathbf{h}) + \text{LS}^*(-\mathbf{D}^*\mathbf{u}, -\mathbf{D}^*\boldsymbol{\ell}) + \mathcal{N}^*(\mathbf{u}, \boldsymbol{\ell}) \end{aligned}$$



- ✓ Significant convergence acceleration
- ✓ Good stopping criterion: $\underline{\delta(\mathbf{v}^n, \mathbf{h}^n; \mathbf{u}^n, \boldsymbol{\ell}^n) \leq 10^{-3}}$

Convex conjugate of data fidelity term

$$\text{LS}^*(\mathbf{v}, \mathbf{h}) = \sup_{\tilde{\mathbf{v}}, \tilde{\mathbf{h}} \in \mathbb{R}^{|\Omega|}} \langle \tilde{\mathbf{v}}, \mathbf{v} \rangle + \langle \tilde{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\tilde{\mathbf{v}}, \tilde{\mathbf{h}}) = \langle \bar{\mathbf{v}}, \mathbf{v} \rangle + \langle \bar{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\bar{\mathbf{v}}, \bar{\mathbf{h}}).$$

(if sup is reached)

Convex conjugate of data fidelity term

$$\text{LS}^*(\mathbf{v}, \mathbf{h}) = \sup_{\substack{\tilde{\mathbf{v}}, \tilde{\mathbf{h}} \in \mathbb{R}^{|\Omega|}}} \langle \tilde{\mathbf{v}}, \mathbf{v} \rangle + \langle \tilde{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\tilde{\mathbf{v}}, \tilde{\mathbf{h}}) = \langle \bar{\mathbf{v}}, \mathbf{v} \rangle + \langle \bar{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\bar{\mathbf{v}}, \bar{\mathbf{h}}). \quad (\text{if sup is reached})$$

Euler condition

$$\begin{cases} \mathbf{v} - 2 \sum_a (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,..}) = 0 \\ \mathbf{h} - 2 \sum_a \log(a) (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,..}) = 0 \end{cases}$$

Convex conjugate of data fidelity term

$$\text{LS}^*(\mathbf{v}, \mathbf{h}) = \sup_{\tilde{\mathbf{v}}, \tilde{\mathbf{h}} \in \mathbb{R}^{|\Omega|}} \langle \tilde{\mathbf{v}}, \mathbf{v} \rangle + \langle \tilde{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\tilde{\mathbf{v}}, \tilde{\mathbf{h}}) = \langle \bar{\mathbf{v}}, \mathbf{v} \rangle + \langle \bar{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\bar{\mathbf{v}}, \bar{\mathbf{h}}). \quad (\text{if sup is reached})$$

Euler condition

$$\begin{cases} \mathbf{v} - 2 \sum_a (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,.}) = 0 \\ \mathbf{h} - 2 \sum_a \log(a) (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,.}) = 0 \end{cases} \iff \mathbf{A}^* \mathbf{A} \begin{pmatrix} \bar{\mathbf{v}} \\ \bar{\mathbf{h}} \end{pmatrix} = \begin{pmatrix} \mathbf{v}/2 + \mathcal{S} \\ \mathbf{h}/2 + \mathcal{T} \end{pmatrix}$$

$$\mathcal{S} = \sum_a \log \mathcal{L}_{a,.} \quad \text{and} \quad \mathcal{T} = \sum_a \log(a) \log \mathcal{L}_{a,.},$$

Convex conjugate of data fidelity term

$$\text{LS}^*(\mathbf{v}, \mathbf{h}) = \sup_{\tilde{\mathbf{v}}, \tilde{\mathbf{h}} \in \mathbb{R}^{|\Omega|}} \langle \tilde{\mathbf{v}}, \mathbf{v} \rangle + \langle \tilde{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\tilde{\mathbf{v}}, \tilde{\mathbf{h}}) = \langle \bar{\mathbf{v}}, \mathbf{v} \rangle + \langle \bar{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\bar{\mathbf{v}}, \bar{\mathbf{h}}). \quad (\text{if sup is reached})$$

Euler condition

$$\begin{cases} \mathbf{v} - 2 \sum_a (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,.}) = 0 \\ \mathbf{h} - 2 \sum_a \log(a) (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,.}) = 0 \end{cases} \iff \mathbf{A}^* \mathbf{A} \begin{pmatrix} \bar{\mathbf{v}} \\ \bar{\mathbf{h}} \end{pmatrix} = \begin{pmatrix} \mathbf{v}/2 + \mathcal{S} \\ \mathbf{h}/2 + \mathcal{T} \end{pmatrix}$$

$$\mathcal{S} = \sum_a \log \mathcal{L}_{a,.} \quad \text{and} \quad \mathcal{T} = \sum_a \log(a) \log \mathcal{L}_{a,.},$$

$$\forall m = \{0, 1, 2\}, \quad \mathbf{A}_m = \sum_a (\log a)^m, \quad \mathbf{A}^* \mathbf{A} = \begin{pmatrix} \mathbf{A}_0 \mathbf{I} & \mathbf{A}_1 \mathbf{I} \\ \mathbf{A}_1 \mathbf{I} & \mathbf{A}_2 \mathbf{I} \end{pmatrix}$$

Convex conjugate of data fidelity term

$$\text{LS}^*(\mathbf{v}, \mathbf{h}) = \sup_{\tilde{\mathbf{v}}, \tilde{\mathbf{h}} \in \mathbb{R}^{|\Omega|}} \langle \tilde{\mathbf{v}}, \mathbf{v} \rangle + \langle \tilde{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\tilde{\mathbf{v}}, \tilde{\mathbf{h}}) = \langle \bar{\mathbf{v}}, \mathbf{v} \rangle + \langle \bar{\mathbf{h}}, \mathbf{h} \rangle - \text{LS}(\bar{\mathbf{v}}, \bar{\mathbf{h}}). \quad (\text{if sup is reached})$$

Euler condition

$$\begin{cases} \mathbf{v} - 2 \sum_a (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,.}) = 0 \\ \mathbf{h} - 2 \sum_a \log(a) (\bar{\mathbf{v}} + \log(a) \bar{\mathbf{h}} - \log \mathcal{L}_{a,.}) = 0 \end{cases} \iff \mathbf{A}^* \mathbf{A} \begin{pmatrix} \bar{\mathbf{v}} \\ \bar{\mathbf{h}} \end{pmatrix} = \begin{pmatrix} \mathbf{v}/2 + \mathcal{S} \\ \mathbf{h}/2 + \mathcal{T} \end{pmatrix}$$

$$\mathcal{S} = \sum_a \log \mathcal{L}_{a,.} \quad \text{and} \quad \mathcal{T} = \sum_a \log(a) \log \mathcal{L}_{a,.},$$

$$\forall m = \{0, 1, 2\}, \quad \mathbf{A}_m = \sum_a (\log a)^m, \quad \mathbf{A}^* \mathbf{A} = \begin{pmatrix} \mathbf{A}_0 \mathbf{I} & \mathbf{A}_1 \mathbf{I} \\ \mathbf{A}_1 \mathbf{I} & \mathbf{A}_2 \mathbf{I} \end{pmatrix}$$

$$\text{LS}^*(\mathbf{v}, \mathbf{h}) = \frac{1}{4} \langle (\mathbf{v}, \mathbf{h}), (\mathbf{A}^* \mathbf{A})^{-1}(\mathbf{v}, \mathbf{h}) \rangle + \langle (\mathcal{S}, \mathcal{T}), (\mathbf{A}^* \mathbf{A})^{-1}(\mathbf{v}, \mathbf{h}) \rangle + \mathcal{C}$$

where \mathcal{C} constant term only depending on $\mathcal{L}(X)$.

Conclusion

Comparison of the different methods

Liquid/Gas (regularity change)	Clear/Dark bubbles (variance change)	Smooth contours
-----------------------------------	---	--------------------

Conclusion

Comparison of the different methods

	Liquid/Gas (regularity change)	Clear/Dark bubbles (variance change)	Smooth contours
Yuan	X	✓	✓

Conclusion

Comparison of the different methods

	Liquid/Gas (regularity change)	Clear/Dark bubbles (variance change)	Smooth contours
Yuan	✗	✓	✓
T-ROF	✓	✓	✗

Conclusion

Comparison of the different methods

	Liquid/Gas (regularity change)	Clear/Dark bubbles (variance change)	Smooth contours
Yuan	✗	✓	✓
T-ROF	✓	✓	✗
Joint	✓	✓	~

Conclusion

Comparison of the different methods

	Liquid/Gas (regularity change)	Clear/Dark bubbles (variance change)	Smooth contours
Yuan	✗	✓	✓
T-ROF	✓	✓	✗
Joint	✓	✓	~
Coupled	✓	✓	✓

Conclusion

Comparison of the different methods

	Liquid/Gas (regularity change)	Clear/Dark bubbles (variance change)	Smooth contours
Yuan	✗	✓	✓
T-ROF	✓	✓	✗
Joint	✓	✓	~
Coupled	✓	✓	✓

Coupled is the most satisfactory in term of segmentation quality ...

Conclusion

Comparison of the different methods

	Liquid/Gas (regularity change)	Clear/Dark bubbles (variance change)	Smooth contours
Yuan	✗	✓	✓
T-ROF	✓	✓	✗
Joint	✓	✓	~
Coupled	✓	✓	✓

Coupled is the most satisfactory in term of segmentation quality ...

... but it is the most time consuming (2100s)
Yuan(1s), T-ROF (12s), Joint (700s)